

## Batteriekontakt / Battery Probe - UEBK-30254 / 30255

### Material (Material)

Gehäuse: Polyamid PA66 (UL94V-2)  
*(Housing: Polyamide PA66 (UL94V-2))*

Kolben: Messing, vergoldet  
*(Plunger: Brass, gold plated)*

Stifthülse: Messing, vergoldet  
*(Barrel: Brass, gold plated)*

Feder: Edelstahl  
*(Spring: Stainless Steel)*

### Elektrische Spezifikation (Electrical specification)

Nennstrom pro Kontakt: 6 A  
*(Rated Current per Contact: 6 A)*

Kontaktwiderstand: < 25 mΩ  
*(Contact Resistance: < 25 mΩ)*

### Mechanische Spezifikation (Mechanical specification)

Kontakte: 4  
*(No. of contacts: 4)*

Max. Hub: 2,65 mm  
*(Max. travel: 2,65 mm)*

Empfohlener Hub: 1,55 mm  
*(Recommended travel: 1,55 mm)*

Federkraft pro Kontakt: 1,2 N bei Empfohlenem Hub  
*(Spring Force per Contact: 1,2 N @ recommended travel)*

Kabelquerschnitt: max. 1,4 mm<sup>2</sup>  
*(Cable cross section: max. 1,4 mm<sup>2</sup>)*

### Bestellinformation (Order Information)

Art. Nr. (Art. No.):  
 UEBK-30254 / UEBK-30255

