

Batteriekontakt / Battery Probe - UEBK-30330

Material (Material)

Gehäuse: Thermoplastik (UL94V-0)

(Frame: Thermoplastic UL94-0)

Kolben: Kupfer, vergoldet

(Plunger: Copper, gold plated)

Stifthülse: Kupfer, vergoldet

(Barrel: Copper, gold plated)

Feder: Edelstahl

(Spring: Stainless Steel)

Elektrische Spezifikation (Electrical specification)

Nennstrom pro Kontakt: 8 A

(Rated Current per Contact: 8 A)

Kontaktwiderstand: < 20 mΩ

(Contact Resistance: < 20 mΩ)

Mechanische Spezifikation (Mechanical specification)

Kontakte: 4

(No. of contacts: 4)

Minimum Raster: 4,00 mm

(Minimum Centers: 4,00 mm)

Max. Hub: 2,29 mm

(Max. travel: 2,29 mm)

Empfohlener Hub: 1,14 mm

(Recommended travel: 1,14 mm)

Federkraft pro Kontakt: 1,2 N bei Empfohlenem Hub

(Spring Force per Contact: 1,2 N @ recommended travel)

Anschluss: THT

(Connection: THT)

Besonderheit: UNC 4 - 40 Gewinde

(Special feature: UNC 4 - 40 thread)

Bestellinformation (Order Information)

Art. Nr. (Art. No.):

UEBK-30330

