



VGRCB-22CPF

VGFCB-22CPF

## **VGRCB-22CPF**

## **VGFCB-22CPF**

The VGRCB-22CPF provides 22 contacts for mini-coax, mini-power or a combination of both contact styles. Coax contacts are provided for signals up to 1 Ghz and power signals up to 50 Amps / 250VAC.

Two precision alignment pins per block ensure proper alignment. Two shoulder mounting screws per VGR block allow the block to float in the receiver. Contacts, blocks and cables sold separately.

### **Coax Contact Pair Specifications**

Voltage .....	250VAC
Current .....	.5 AMP
Contact Resistance .....	5mΩ
Impedance.....	50Ω
Capacitance.....	21pf
Inductance .....	3nH
Bandwidth (-3db roll off) .....	1 Ghz
Durability.....	25,000 cycles
Coax Connection Type .....	Crimp

### **Power Contact Pair Specifications**

Power Contact (8AWG std) .....	50 Amp
--------------------------------	--------

### **Ordering Information**

#### **Receiver**

Receiver Module.....	VGRCB-22CPF
36" Receiver Coax Cable Assy.....	CR-MCA50RG174-36
Receiver Mini Coax Contact .....	CR-610104114
Receiver Mini Power Contact .....	CR-610116112

#### **Fixture**

Fixture Module .....	VGFCB-22CPF
36" Fixture Coax Cable Assy.....	CF-MCA50RG174-36
Fixture Mini Coax Contact.....	CF-610103115
Fixture Mini Power Contact .....	CF-0883011-02

### **Accessories**

Receiver / Fixture Contact Extraction Tool .....	VGMXT
--	-------

